




# Power Supplies MJ-1240 Specification

## Model: MJ-1240



- Features

---

**40 Watts Max, 12VDC Constant Voltage Output**

---

**Suitable in standard electrical 4X4 junction boxes**

---

**Suitable for Dry or Damp Locations, IP66 , NEMA4**

---

**Convection Cooled, Plastic Housing,**

---

**Class 2 , FCC,CE Certified**

---

**3 Years Warranty**

### Specifications

Input Voltage Range : 90 ~ 264Vac	Operation Temp. : - 30 ~ +60 °C
Input Frequency Range : 47 ~ 63Hz	Temp.De-rating : 1% per °C at 60 ~ 70°C %
Input Inrush Current : < 5A/115V, 10A/ 230V	Storage Temp. : - 40°C ~ + 85°C
Power Factor : > 0.9 at Full Load, 115Vac	Humidity (Non – Condensing) : 5% ~ 90%
Leakage Current : 300uA Typical	Vibration Frequency : 5 ~ 50 Hz, Shock : MIL-STD-810E
Efficiency : 84 % Typical at full	MTBF ( @25 °C ) : >100,000 Hours. MIL-217F
Protection : OCP , OVP ,SCP – Auto Recovery	Compliance – 47CFR Part 2 and CISPR B , CE

- Model Listing

Model	Working Voltage	DC Output Current ( A )	MAX. Watts	OCP ( A )	OVP ( V )	Regulation	
						Load	Line
MJ-1240	12V	0 ~ 3.33	40	5.2	15~18	3%	1%